

GOTECH "the best partner" to raise your competition

GT-7037-H 安全鞋衝擊試驗機 Safety Footwear Impact Tester

CSA Z195-2014 6.2 6.4、ASTM F2412-18a 5.0 7.0、ASTM F2413-18 5.1 5.4

適用於安全鞋、防護鞋和職業鞋，也適用於其他用於個體防護的鞋類安全性能試驗方法，腳趾保護抗衝擊性能試驗及其跖骨保護裝置抗衝擊性能試驗。

This machine, incorporating a steel striker adapted to fall freely on vertical guides from a predetermined height to give the required impact energy to the toe of safety footwear for measuring the degree of the dent. In addition, the toecap should not develop any cracks on the test axis with go through the material.

衝擊器重量 Mass of striker	5kg、20.0kg、22.7kg
衝擊能量範圍 Impact energy range	最大220J (衝擊器重量 Mass of striker≥20kg時)
衝擊行程範圍 Impact stroke range	100mm~1200mm
體積(約) Dimension (W×D×H)	主機 Main unit 83 cm ×60 cm ×235 cm
	控制箱 Control cabinet 27 cm ×27 cm ×115 cm
重量(約) Weight (approx.)	240kg
	※備註：客戶處需自備儀器安裝地基，確保儀器穩定性 Note: Requiring foundation to ensure the stability of tester.
電源 Power	1φ AC 220V 50Hz(依國別或指定 or specify)



瞭解更多產品資訊，請登錄我司網站 www.gotech.biz