

GOTECH "the best partner" to raise your competition

GT-7010-D2E 微電腦拉力試驗機 Micro-computer tensile strength tester

本機用途廣泛，更換不同夾具可測試各種材料及鞋底、輪胎、橡膠管、三角膠帶、塑膠布、塑膠板、包裝用薄膜、壓克力、FRP、ABS、EVA、PV等成品、半成品或啞鈴狀試片之抗拉強度、伸長、撕裂、膠著力、抗拉應力、剝離、剪力、橡膠與金屬之黏接力。本機為電子顯示拉力試驗機，運用馬達傳動螺桿而使下夾具向下移動，因而拉伸試料；結果運用LOAD CELL力量感應器連接數字顯示器顯示力量值。

This equipment is widely used for testing the tensile strength, elongation, tear resistance, cohesive force, tensile stress, peel force, shear force, adhesive force and so forth of various materials and the finished products, semi-finished products or dumbbell-type specimens of the soles, tires, rubber tubes, triangle adhesive tapes, plastic fabrics, plastic plates, metals, packing films, acryl, FRP, ABS, EVA, PV, etc. This equipment belongs to electronic type tensile machine. The lower grip of this equipment moves downwards as a result of the motor drives the screw so that the specimen is elongated. The test value will show on the display through the Load cell.



感應方式 Sensor	LOAD CELL力量感應器
顯示器配置 Display device	U26
容量 Capacity	100 · 200 · 500 N ; 1 · 2 · 5 kN 供選擇 optional
單位切換 Unit (changeable)	Kgf, gf, tonf, lbf, N, kN
分解度 Load resolution	1 / 50,000
試驗力示值誤差 Load accuracy	±0.5%
位移精度 Stoke accuracy	0.01 mm
測試速度 Test speed	5 ~ 500 mm/min 可調 adjustable
馬達 Motor	AC伺服馬達 AC servo motor
速度輸入方式 Speed control method	面板輸入 · 閉迴路控速 Closed-loop speed control
顯示器 Indicator	顯示伸長量、測試值、斷裂值、最高值 displaying elongation value 、test value 、breaking value 、max. value
體積 Dimension(W×D×H)	55×35×182 cm
電源 Power	1φ AC 220V 5A(依國別或指定 or specify)

瞭解更多產品資訊，請登錄我司網站 www.gotech.biz