

GOTECH "the best partner" to raise your competition

GT-7013-AD 破裂強度試驗機 Bursting Strength Tester

ASTM-D2210、JIS-L1018、JIS-P8112、TAPPI-T403、JIS-L1004

本機適用於紙箱、紙板、布類及皮革之破裂強度測試。將試樣置於上、下壓盤間夾緊，利用馬達注入甘油均勻施加壓力，使試樣與橡皮膜一起凸起，直至試樣破裂為止，試樣耐破度是施加液壓的最大值。

The GT-7013-AD is designed to assess the bursting strength of materials such as corrugated paper, leather, and fabrics. The sample is inflated using motor-controlled hydraulic pressure, and the maximum break force is detected upon sample failure.



型式 Model	高壓式 High pressure	低壓式 Low pressure	高壓式低速率
規範 Conformance	GB/T 1539	ISO 2758, GB/T 454, TAPPI T403	ASTM D3786, ASTM D3786M-18
容量 Capacity	100 kg/cm²	16 kgf/cm²	100 kg/cm²
夾持力 Clamping force	0 ~ 50 kgf/cm²(可調 adjustable) 0 ~ 25 kgf/cm² (可調 adjustable)		
加壓速度 Pressing speed	170±15 mL/min	95±5 ml/min	
感應方式 Sensing method	壓力傳感器 Pressure transducers		
顯示器 Indicator	U20		
上夾盤內徑 Inner dia. of upper clamp	31.5 mm	30.48 mm	31±0.75 mm
下夾盤內徑 Inner dia. of lower clamp	31.5 mm	33.1±0.1 mm	31±0.75 mm
電源 Power	1φ · AC220V · 50/60Hz · 3A (依國別或指定 or specify)		

瞭解更多產品資訊，請登錄我司網站 www.gotech.biz